



SOLAR RATING & CERTIFICATION CORPORATION

CERTIFIED SOLAR COLLECTOR

SUPPLIER:
Viessmann Manufacturing Company (US) Inc.
 45 Access Road
 Warwick, RI 02886 USA
 www.viessmann-us.com
 In Accordance with:
SRCC Standard 100-2013-01

BRAND: Vitosol
 MODEL: 200-T SPE - 1.63
 COLLECTOR TYPE: Tubular
 CERTIFICATION #: 10001827
 Original Certification: October 13, 2015
 Expiration Date: July 30, 2027

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

COLLECTOR THERMAL PERFORMANCE RATING							
Kilowatt-hours (thermal) Per Panel Per Day				Thousands of Btu Per Panel Per Day			
Climate ->	High Radiation (6.3 kWh/m ² .day)	Medium Radiation (4.7 kWh/m ² .day)	Low Radiation (3.1 kWh/m ² .day)	Climate ->	High Radiation (2000 Btu/ft ² .day)	Medium Radiation (1500 Btu/ft ² .day)	Low Radiation (1000 Btu/ft ² .day)
Category (Ti-Ta)				Category (Ti-Ta)			
A (-5 °C)	7.1	5.3	3.6	A (-9 °F)	24.1	18.2	12.3
B (5 °C)	6.7	5.0	3.3	B (9 °F)	22.9	17.1	11.2
C (20 °C)	6.2	4.4	2.7	C (36 °F)	21.0	15.2	9.3
D (50 °C)	5.1	3.4	1.7	D (90 °F)	17.3	11.5	5.8
E (80 °C)	3.8	2.2	0.7	E (144 °F)	12.9	7.6	2.5

A- Pool Heating (Warm Climate) B- Pool Heating (Cool Climate) C- Water Heating (Warm Climate)
 D- Space & Water Heating (Cool Climate) E- Commercial Hot Water & Cooling

COLLECTOR SPECIFICATIONS					
Gross Area:	2.757 m ²	29.68 ft ²	Dry Weight:	57 kg	126 lb
Net Aperture Area:	1.727 m ²	18.59 ft ²	Fluid Capacity:	0.5 liter	0.1 gal
Absorber Area:	1.631 m ²	17.56 ft ²	Test Pressure:	900 kPa	131 psi

TECHNICAL INFORMATION			Tested in accordance with: ISO 9806:1994		
ISO Efficiency Equation [NOTE: Based on gross area and (P)=Ti-Ta]					
SI UNITS:	$\eta = 0.432 - 1.10340(P/G) - 0.00470(P^2/G)$	Y Intercept:	0.434	Slope:	-1.411 W/m ² .°C
IP UNITS:	$\eta = 0.432 - 0.19447(P/G) - 0.00046(P^2/G)$	Y Intercept:	0.434	Slope:	-0.249 Btu/hr.ft ² .°F

Transverse Incident Angle Modifier								Longitudinal Incident Angle Modifier at 50°:		0.91
θ	10	20	30	40	50	60	70	Test Fluid:	Water	
K_{τα}	1.01	1.02	1.03	1.03	0.98	0.96	0.70	Test Mass Flow Rate:	0.0182 kg/(s m ²)	13.42 lb/(hr ft ²)

REMARKS:

Jen Higgins

Technical Director

Print Date: October, 2015 Page 1 of 4
 Please verify certification is active on the SRCC website.
 © Solar Rating & Certification Corporation™



CERTIFIED SOLAR COLLECTOR



SOLAR RATING
& CERTIFICATION
CORPORATION

SUPPLIER:
Viessmann Manufacturing Company (US) Inc.
45 Access Road
Warwick, RI 02886 USA
www.viessmann-us.com

In Accordance with:
SRCC Standard 100-2013-01

BRAND: Vitosol
MODEL: 200-T SPE - 1.63
COLLECTOR TYPE: Tubular
CERTIFICATION #: 10001827
Original Certification: October 13, 2015
Expiration Date: July 30, 2027

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

ADDITIONAL INFORMATION (click here to return to the rating page)			
Test Lab:	TÜV Rheinland Energie und Umwelt GmbH	Test Date:	July 30, 2015
Test Report Number:	21227426.001	Test Location:	outdoors

SOLAR COLLECTOR CONSTRUCTION DETAILS					
Header Enclosure:					
Gross Length:	2.260 m	Gross Width:	1.220 m	Gross Depth:	0.174 m
Tube Bank:					
Gross Length:	0.217 m	Gross Width:	2.390 m		

COLLECTOR MATERIALS					
Outer Cover:	Glass Tube	Enclosure back:	None	Back Insulation:	Vacuum,
Inner Cover:	None	Enclosure side:	None	Side Insulation:	,
Absorber Description:	Tubes connected to Fins		Flow Pattern:	Series/Meander	
Riser Tube:	Copper		Fin:	Aluminum	
Absorber Coating:	Selective		Tube to fin connection	Ultrasonic Weld	

GLAZING	Outer Cover	Inner Cover
Material:	Glass Tube	None
Surface Characteristics:	Smooth	
Thickness:	2.8 mm	N/A
Transmissivity:	High (equal to or greater than 90%)	
Gross Tube Length (uninstalled):	2.050 m	
Diameter:	0.102 m	
Tube Glazing to Header Enclosure Seal:	EPDM gasket	
Reflector Shape:		Reflector Material:



Print Date: October, 2015 Page 2 of 4
Please verify certification is active on the SRCC website.
© Solar Rating & Certification Corporation™

CERTIFIED SOLAR COLLECTOR



SOLAR RATING
& CERTIFICATION
CORPORATION

SUPPLIER:
Viessmann Manufacturing Company (US) Inc.
45 Access Road
Warwick, RI 02886 USA
www.viessmann-us.com

In Accordance with:
SRCC Standard 100-2013-01

BRAND: Vitosol
MODEL: 200-T SPE - 1.63
COLLECTOR TYPE: Tubular
CERTIFICATION #: 10001827
Original Certification: October 13, 2015
Expiration Date: July 30, 2027

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

ABSORBER					
Header Material:		Header OD:		Header Wall:	
Riser Tube Material:	Copper	Riser Tube OD:	12.0 mm	Riser Tube Wall Thickness:	0.9 mm
Fin Material:	Aluminum	Fin Thickness:	0.30 mm		
Flow Pattern:	Series/Meander	Number of Flow Tubes / Heat Pipes:	9	Tube / Heat Pipe Spacing:	130.0 mm
Number of absorber tubes:	1	Flow Tube to Fin Bond:	Ultrasonic Weld	Length of Flow Path:	
Length of Flow Path:		Riser to Fin/Plate Bond:	Ultrasonic Weld		

INSULATION:					
Location	Type	Thickness	Location	Type	Thickness
Back – Top Layer:	Vacuum	42.2 mm	Sides – Inner Layer:		
Back – Bottom Layer:			Sides – Outer Layer:		
Enclosure Fastening Methods:	Other		Header Enclosure:	Aluminum with plastic ends	

Power Output per Collector(W) [Ti-Ta, G = 1000 W/m²]				
0	10	30	50	70
1192	1160	1089	1007	915



Print Date: October, 2015 Page 3 of 4
Please verify certification is active on the SRCC website.
© Solar Rating & Certification Corporation™

CERTIFIED SOLAR COLLECTOR



SOLAR RATING
& CERTIFICATION
CORPORATION

SUPPLIER:
Viessmann Manufacturing Company (US) Inc.
45 Access Road
Warwick, RI 02886 USA
www.viessmann-us.com

In Accordance with:
SRCC Standard 100-2013-01

BRAND: Vitosol
MODEL: 200-T SPE - 1.63
COLLECTOR TYPE: Tubular
CERTIFICATION #: 10001827
Original Certification: October 13, 2015
Expiration Date: July 30, 2027

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ISO/IEC 17065 accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference. This document must be reproduced in its entirety.

PRESSURE DROP				
Flow	ΔP		Flow	ΔP
ml/s	Pa		gpm	in H ₂ O
20	0		0.32	0.0
50	0		0.79	0.0
80	0		1.27	0.0



Print Date: October, 2015 Page 4 of 4
Please verify certification is active on the SRCC website.
© Solar Rating & Certification Corporation™